

INDUSTRIAL COMPONENT DATA

Low Voltage British Standard TB63M80 EATON ELECTRIC Fuse-link, low voltage, 63, AC 415 V, BS88, 27 x 112 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: Low Voltage - British Standard



Manufacturer	EATON - MOELLER
MPN / Reference	Low Voltage - British Standard
Catalog number	TB63M80
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-B7805520C6
Generated	2026-08-05

Product Overview

Fuse-link, low voltage, 63, AC 415 V, BS88, 27 x 112 mm, gM, BS, 63M80

63M80 415V AC INDUSTRIAL

Fuse, Fuse-link, low voltage, AC 415 V, BS88, 27 x 112 mm, gM, BS, centre-bolted tags, motor-rated, general industrial applications, BS88, IEC 60269, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 63, AC 415 V, BS88, 27 x 112 mm, gM, BS, 63M80 Fuse, Fuse-link, low voltage, AC 415 V, BS88, 27 x 112 mm, gM, BS, centre-bolted tags, motor-rated, general industrial applications, BS88, IEC 60269, Breaking Capacity 80 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Motor current rating [I] 63M80 A Rated voltage AC 415 V Construction size BS88 Size 27 x 112 mm Utilization category gM Description motor-rated Breaking Capacity 80 kA usable for size/applications general industrial applications Standard/Approval BS Shape centre-bolted tags Standards/Regulations BS88

IEC 60269 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 63 A Rated voltage 660 V Voltage type AC Rated switching capacity 80 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No

ETIM for TB63M80 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Rated current (EF000227)

80 A

Utilization category according to IEC 60269 (EF002572)

Other

Breaking capacity (EF005617)

80 kA

Type of fuse status indicator (EF004473)

None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Low Voltage - British Standard with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.