

INDUSTRIAL COMPONENT DATA

Low Voltage British Standard TLT800 EATON ELECTRIC Fuse-link, low voltage, 800 A, AC 660 V, DC 350 V, BS88, ..

Brand: EATON - MOELLER | Manufacturer Part Number: Low Voltage - British Standard



Manufacturer	EATON - MOELLER
MPN / Reference	Low Voltage - British Standard
Catalog number	TLT800
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-71EFEF04CE
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 800 A, AC 660 V, DC 350 V, BS88, gL/gG, BS, IEC

800AMP 415V AC / 250V DC

Fuse, Fuse-link, low voltage, 800 A, AC 660 V, DC 350 V, BS88, gL/gG, BS, IEC, centre-bolted tags, 165 mm fixing centres, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series Low Voltage fuses and accessories
--------------	--

Additional Product Information

Fuse-link, low voltage, 800 A, AC 660 V, DC 350 V, BS88, gL/gG, BS, IEC Fuse, Fuse-link, low voltage, 800 A, AC 660 V, DC 350 V, BS88, gL/gG, BS, IEC, centre-bolted tags, 165 mm fixing centres, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 800 A Rated voltage AC 660 V

DC 350 V Construction size BS88 Utilization category gL/gG Description 165 mm fixing centres Breaking Capacity 80 kA usable for size/applications general industrial applications Standard/Approval BS

IEC Shape centre-bolted tags Standards/Regulations BS88-2

IEC 60269-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 800 A Rated voltage 660 V Voltage type AC/DC Rated switching

capacity 80 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None

Insulated metal gripping lugs (IMGL) No

ETIM for TLT800 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

800 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Low Voltage - British Standard with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.