

INDUSTRIAL COMPONENT DATA

Low Voltage British Standard TT560 EATON ELECTRIC Fuse-link, low voltage, 560 A, AC 660 V, BS88, 73 x 267 mm..

Brand: EATON - MOELLER | Manufacturer Part Number: Low Voltage - British Standard



Manufacturer	EATON - MOELLER
MPN / Reference	Low Voltage - British Standard
Catalog number	TT560
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-90D8B80582
Generated	2026-08-05

Product Overview

Fuse-link, low voltage, 560 A, AC 660 V, BS88, 73 x 267 mm, gL/gG, BS

560AMP 415V AC / 400V DC

Fuse, Fuse-link, low voltage, 560 A, AC 660 V, BS88, 73 x 267 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

Fuse-link, low voltage, 560 A, AC 660 V, BS88, 73 x 267 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 560 A, AC 660 V, BS88, 73 x 267 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 560 A Rated voltage AC 660 V Construction size BS88 Size 73 x 267 mm Utilization category gL/gG Breaking Capacity 80 kA usable for size/applications general industrial applications Standard/Approval BS Shape centre-bolted tags Standards/Regulations BS88-2

IEC 60269-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 560 A Rated voltage 660 V Voltage type AC Rated switching capacity 80 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal

gripping lugs (IMGL) No
ETIM for TT560 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Rated current (EF000227)
560 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacity (EF005617)
80 kA
Type of fuse status indicator (EF004473)
None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Low Voltage - British Standard with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.