

INDUSTRIAL COMPONENT DATA

Low Voltage NH 200NHM1B EATON ELECTRIC Low-voltage h.b.c fuse switch strip, 160A, size 00

Brand: EATON - MOELLER | Manufacturer Part Number: Low Voltage - NH



Manufacturer	EATON - MOELLER
MPN / Reference	Low Voltage - NH
Catalog number	200NHM1B
Category	Low Voltage HRC fuse
Minimum order	1 Pcs
Document ID	EO-59CDA63BC4
Generated	2026-08-05

Product Overview

Low-voltage h.b.c fuse switch strip, 160A, size 00

FUSE NH SIZE 1 AM 200A 500V

200NHM1B - Fuse-link, LV, 200 A, AC 500 V, NH1, aM, IEC, dual indicator, live gripping lugs

Fuse, Fuse-link, low voltage, 200 A, AC 500 V, NH1, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, LV, 200 A, AC 500 V, NH1, aM, IEC, dual indicator, live gripping lugs Fuse, Fuse-link, low voltage, 200 A, AC 500 V, NH1, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 200 A Rated voltage AC 500 V Construction size NH1 Utilization category aM Status indicator dual (combination) indicator system Description live gripping lugs Breaking Capacity 120 kA Standard/Approval IEC Shape square body with knife blade contacts

Standards/Regulations IEC 60269-2 fuse system A

DIN 43620

VDE 0636-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size NH1 Rated current 200 A Rated voltage 500 V Voltage type AC Rated switching capacity 120 kA Utilization category aM (switchgear protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) No
ETIM for 200NHM1B Circuit breakers and fuses (EC000055)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
NH1
Voltage type (EF000187)
AC
Rated current (EF000227)
200 A
Utilization category a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Low Voltage - NH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.