

INDUSTRIAL COMPONENT DATA

NH FUSE 250A 690V AC gG SIZE 1 250NHG1BI-690 EATON ELECTRIC Fuse-link, LV, 250 A, AC 690V, NH1, gL/gG, IEC, ..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 250A 690V AC gG SIZE 1



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 250A 690V AC gG SIZE 1
Catalog number	250NHG1BI-690
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-58071058F1
Generated	2026-08-06

Product Overview

Fuse-link, LV, 250 A, AC 690V, NH1, gL/gG, IEC, dual indicator, insulated gripping lugs

NH FUSE 250Amp 690V AC gG SIZE 1

NH FUSE 250Amp 690V AC gG SIZE 1 - Fuse-link, low voltage, 250 A, AC 690 V, 120 kA, NH1, gG/gL, IEC, dual indicator, insulated gripping lugs

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 250 A, AC 690 V, 120 kA, NH1, gG/gL, IEC, dual indicator, insulated gripping lugs
Fuse, Fuse-link, low voltage, 250 A, AC 690 V, NH1, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I]_N 250 A
Rated voltage AC 690 V
Construction size NH1
Utilization category gG/gL
Status indicator dual indicator
Description insulated gripping lugs
Breaking Capacity 120 kA
Usable for size/applications industrial
Standard/Approval IEC
Shapes square-body with knife blade contacts
Standards/Regulations IEC 60269-1
Optional accessories fuse-holder SD1-D
Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [I]_N 250 A
Equipment heat dissipation, current-dependent [P_{vid}] 22 W
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeNH1Rated current250 ARated voltage690 VVoltage typeACRated switching capacity120
kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorCombination fuse status
indicatorInsulated metal gripping lugs (IMGL)Yes
ETIM for 250NHG1BI-690 Circ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 250A 690V AC gG SIZE 1 with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.