

INDUSTRIAL COMPONENT DATA

NH FUSE 315A 690V GG SIZE 2 315NHG2BI-690 EATON

ELECTRIC Fuse-link, LV, 315 A, AC 500 V, NH2, gL/gG, IEC, du..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 315A 690V GG SIZE 2



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 315A 690V GG SIZE 2
Catalog number	315NHG2BI-690
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-42077847AE
Generated	2026-08-06

Product Overview

Fuse-link, LV, 315 A, AC 500 V, NH2, gL/gG, IEC, dual indicator, insulated gripping lugs
NH FUSE 315A 690V GG SIZE 2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH Fuse Catalog Number 315NHG2BI-690 Model Code NH FUSE 315A 690V GG SIZE 2 EAN 5027590476492 Product Length/Depth 150 mm Product Height 71 mm Product Width 54 mm Product Weight 651 g Compliances RoHS Compliant

CE Marked Certifications IEC 60269-1

IEC 60269-2

DIN 43620 Electrical data

Amperage Rating 315 A Voltage rating 690 V Voltage type AC Breaking capacity 120 kA Class Class gG/gL Frequency rating - min 45 Hz Frequency rating - max 62 Hz Product specification

Fuse size NH4 Insulated metal gripping lugs (IMGL) Yes Accessories

Suitable for SD4-S NH Fuse base

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

ETIM for 315NHG2BI-690 Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH2

Voltage type (EF000187)

AC

Rated current (EF000227)

315 A

Rated voltage AC (EF007682)

690 V

Rated switching capacity AC (EF017698)

120 kA

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Type of fuse status indicator (EF004473)

Combination fuse status indicator

Insulated metal gripping lugs (IMGL) (EF012538)

Yes

Power loss at rated current (EF012389)

32 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 315A 690V GG SIZE 2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.