

INDUSTRIAL COMPONENT DATA

Low Voltage NH 35NHG000BI-690 EATON ELECTRIC

Low-voltage h.b.c fuse switch strip, 160A, size 00

Brand: EATON - MOELLER | Manufacturer Part Number: Low Voltage - NH



Manufacturer	EATON - MOELLER
MPN / Reference	Low Voltage - NH
Catalog number	35NHG000BI-690
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-9C10BE3333
Generated	2026-08-05

Product Overview

Low-voltage h.b.c fuse switch strip, 160A, size 00

NH FUSE 35AMP 690V SIZE 000 GG IMGL

NH FUSE 35AMP 690V SIZE 000 GG IMGL - Fuse-link, LV, 35 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs

Fuse-link, low voltage, 35 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, LV, 35 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs Fuse, Fuse-link, low voltage, 35A, AC 690 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015] Construction size NH000 Rated current 35 A Rated voltage 690 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) Yes

ETIM for 35NHG000BI-690 Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH000

Voltage type (EF000187)

AC

Rated current (EF000227)

35 A

Rated voltage AC (EF007682)

690 V

Rated switching capacity AC (EF017698)

120 kA

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Type of fuse status indicator (EF004473)

Combination fuse status indicator

Insulated metal gripping lugs (IMGL) (EF012538)

Yes

Power loss at rated current (EF012389)

4 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Low Voltage - NH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.