

INDUSTRIAL COMPONENT DATA

EBH2O3TM1-F EATON ELECTRIC Low-voltage h.b.c fuse switch strip, 160A, size 00

Brand: EATON - MOELLER | Manufacturer Part Number: EBH2O3TM1-F



Manufacturer	EATON - MOELLER
MPN / Reference	EBH2O3TM1-F
Catalog number	10000
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-748DA95D68
Generated	2026-08-06

Product Overview

SIZE 2 HOR FSD, M/PLATE:M10 SCREW+M/S

SIZE 2 HOR FSD, M/PLATE:M10 SCREW+M/S - Switch disconnecter, 400 A, AC 690 V, NH2, IEC, mounting plate type, with microswitch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Switch disconnecter, 400 A, AC 690 V, NH2, IEC, mounting plate type, with microswitch Fuse accessory, Switch disconnecter, low voltage, 400 A, AC 690 V, NH2, AC23B, 3P, IEC, Horizontal, mounting plate type, M10 screws, NH2 fuse-links, IEC 60947-1, IEC 60947-3, IP20, with microswitch Delivery program

Product range Fuse accessory Basic function Switch disconnecter Rated current [I]_N 400 A Rated voltage AC 690 V Construction size NH2 Description mounting plate type with microswitch lug terminal

M10 screws Standard/Approval IEC Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter () [AKF058013]) Version as main switch No Version as safety switch No Max. rated operation voltage U_e AC 690 V Rated permanent current I_u 400 A Rated operation power at AC-23, 400 V 160 kW Conditioned rated short-circuit current I_q 80 kA Rated short-time withstand current I_{cs} 80 kA Suitable for fuses NH2 Number of poles 3 With error

protectionNoType of electrical connection of main circuitScrew connectionCable entryOtherEquipped with
connectorsYesSuitable for ground mountingNoSuitable for front mounting 4-holeYesSuitable for busbar mountingNoType of
control elementCover gripPosition control elementFront sideMotor drive optionalNoMotor drive integratedNoVersion as
emergency stop installationNoDegree of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBH2O3TM1-F with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.