

INDUSTRIAL COMPONENT DATA

LS-S11-CC-ZB 177191 Y7-177191 EATON ELECTRIC Position switches, 1N/C+1N/O, rounded plunger, +actuator ZB, Co..

Brand: EATON - MOELLER | Manufacturer Part Number: LS-S11-CC-ZB



Manufacturer	EATON - MOELLER
MPN / Reference	LS-S11-CC-ZB
Catalog number	Y7-177191
Category	End switch
Minimum order	1 Pcs
Document ID	EO-08D9D30B28
Generated	2026-08-06

Product Overview

Position switches, 1N/C+1N/O, rounded plunger, +actuator ZB, Cold Climate -40°C

LS-S11-CC-ZB

Eaton Moeller® series LS Position switches, 1N/C+1N/O, rounded plunger, +actuator ZB, Cold Climate -40°C

LS-S11-CC-ZB

Position switch, Basic function: Position switches, Safety position switches, Part group reference: LS(4)...ZB, Product range: Safety position switches, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -40 - +70 °C, Description: With the actuator inserted, the N/O contact is open and the NC contact is closed., Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Position switch Catalog Number 177191 Model Code LS-S11-CC-ZB EAN 4015081716357 Product Length/Depth 96 mm Product Height 34 mm Product Width 31 mm Product Weight 0.08 kg

Certifications IEC/EN 60947 Catalog Notes Features & Functions

Electric connection type Cable entry metrical Enclosure material Plastic

Insulated material Features Forced opening Switch function type Slow-action switch General

Connection type Screw terminal Degree of protection IP65

NEMA Other Operating frequency 1800 Operations/h Overvoltage category III Pollution degree 3 Product category Safety position switches Rated impulse withstand voltage (Uimp) 4000 V AC Repetition accuracy 0.15 mm (Contacts/switching capacity) Suitable for Safety functions Type Position switch

Safety position switch

Ambient conditions, mechanical

Mounting position Vertical

Horizontal

As required Shock resistance 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.5 - 1.5) mm²

2 x (0.5 - 1.5) mm² Terminal capacity (solid) 2 x (0.5 - 1.5) mm²

1 x (0.5 - 1.5) mm² Screw size PH1, Terminal screw Electrical rating

Rated insulation voltage (Ui) 400 V Rated operational current (Ie) a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-S11-CC-ZB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.