

INDUSTRIAL COMPONENT DATA

LSC01-20-L20(24V50HZ) 106145 XTST020C00U020NL EATON ELECTRIC Starter for lamp load HQ, L20A

Brand: EATON - MOELLER | Manufacturer Part Number: LSC01-20-L20(24V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	LSC01-20-L20(24V50HZ)
Catalog number	XTST020C00U020NL
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-4329F2425B
Generated	2026-08-06

Product Overview

Starter for lamp load HQ, L20A

Starter for loads of lamps HQL; 20A; 24 V, 50 Hz; In adapter for busbar

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

Starter for lamp load HQ, L20APremounted starter for lamp test on busbar adapter with mounting time advantagesTechnical data

GeneralStandards

UL 508 (on request)

CSA C 22.2 No. 14 (on request)Ambient temperature-25 - +55Main conducting pathsRated impulse withstand voltage

[Uimp]6000 V ACOvertoltage category/pollution degreeIII/3Rated operational voltage [Ue]230 - 415 VAdditional technical

dataMotor protective circuit breaker PKZM0, PKEPKZM0 motor-protective circuit-breakers, see motor-protective circuit-breakers/PKZM0 product group

DILM contactors, see contactor product group

DILET timing relay, ETR, see contactors, electronic timing relays product groupDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]20 AHeat dissipation per

pole, current-dependent [Pvid]2.6 WEquipment heat dissipation, current-dependent [Pvid]7.8 WStatic heat dissipation,

non-current-dependent [Pvs]2.1 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating

ambient temperature max.+55 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion

resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard'...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSC01-20-L20(24V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.