

INDUSTRIAL COMPONENT DATA

LSM-20A 100051 Y7-100051 EATON ELECTRIC Position switch, 2N/O delayed, +rounded plunger

Brand: EATON - MOELLER | Manufacturer Part Number: LSM-20A



Manufacturer	EATON - MOELLER
MPN / Reference	LSM-20A
Catalog number	Y7-100051
Category	End switch
Minimum order	2 Pcs
Document ID	EO-257FF9535E
Generated	2026-08-02

Product Overview

Position switch, 2N/O delayed, +rounded plunger

LSM-20A

Eaton Moeller® series LSM Position switch, Rounded plunger, Basic device, expandable, 2 N/O, Cage Clamp, Yellow, Metal, -25 - +70 °C, version A

Position switch, Basic function: Position switches, Part group reference: LS(M)-..., Product range: Rounded plunger, Degree of Protection: IP66, IP67, Features: Basic device, expandable, Ambient temperature: -25 - +70 °C, Contacts N/O = Normally open: 2 N/O, Color Enclosure covers: Yellow, Housing: Metal, Connection type: Cage Clamp, Cage-Clamp is a registered trademark of Wago Kontakttechnik, 32432 Minden, Germany., Accessories for the Cage-Clamp terminals from Wago:power comb, gray, Wago Article No. 264-402, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Position Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series LSM Position switch Catalog Number 100051 Model Code LSM-20A EAN

4015081000418 Product Length/Depth 33.5 mm Product Height 76.5 mm Product Width 31 mm Product Weight 0.147 kg

Certifications CSA File No.: 012528

UL

CSA-C22.2 No. 14

CSA Class No.: 3211-03

UL 508

IEC/EN 60947

CE

CSA

UL Category Control No.: NKCR

IEC/EN 60947-5

UL File No.: E29184 Features & Functions

Electric connection type Cable entry metrical Enclosure color Yellow Cover Enclosure material Metal Features Expandable

Switch function type Slow-action switch General

Connection type Cage Clamp Degree of protection IP66/IP67

NEMA Other Operating frequency 6000 Operations/h Overvoltage category III Pollution degree 3 Product category

Rounded plunger Rated impulse withstand voltage (Uimp) 4000 V AC Repetition accuracy 0.15 mm (Contacts/switching capacity) Type Position switch Ambient conditions, mechanical

Mounting position As required Shock resistance 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms

Temperature resistance 100 °C, Contact temperature of roller head Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.5 - 1.5) mm² Terminal capacity (solid) 1 x (0.5 - 2.5) mm² Electrical rating

Rated conditional sh...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSM-20A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.