

INDUSTRIAL COMPONENT DATA

LSR-S02-1-I-CC/TKG 169825 EATON ELECTRIC Safety door flap switch for cold climates

Brand: EATON - MOELLER | Manufacturer Part Number: LSR-S02-1-I-CC/TKG



Manufacturer	EATON - MOELLER
MPN / Reference	LSR-S02-1-I-CC/TKG
Catalog number	169825
Category	End switch
Minimum order	1 Pcs
Document ID	EO-9D4FC9EF07
Generated	2026-08-05

Product Overview

Safety door flap switch for cold climates

Safety position switch Plastic 2 NC For hinge Cold weather -40°C

Hasp-operated safety switch, LSR, Hasp-operated safety switch, 2 NC, Screw terminal, -40 - +70 °C

Hasp-operated safety switch, Basic function: Position switches, Safety position switches, Part group reference: LSR,

Product range: Hasp-operated safety switch, Degree of Protection: IP65, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Hasp-operated safety switch, LSR, Hasp-operated safety switch, 2 NC, Screw terminal, -40 - +70 °C Hasp-operated safety switch, Basic function: Position switches, Safety position switches, Part group reference: LSR, Product range:

Hasp-operated safety switch, Degree of Protection: IP65, Standards: IEC/EN 60947 Delivery program

Basic function Position switches

Safety position switches Part group reference LSR Product range Hasp-operated safety switch Degree of Protection IP65

Ambient temperature -40 - +70 °C Approval Contacts N/C = Normally closed 2 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Connection type Screw terminal Technical data

General Standards IEC/EN 60947 Climatic proofing Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30 Ambient temperature -40 - +70 °C Mounting position As required Degree of Protection IP65 Terminal

capacitiesSolid 1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm² Terminal capacitiesFlexible with ferrule 1 x (0.5 - 1.5)

2 x (0.5 - 1.5) mm² Repetition accuracy 0.02 mm Contacts/switching capacity Rated impulse withstand voltage [Uimp] 6000 V AC Rated insulation voltage [Ui] 500 V Rated operational current [Ie]AC-1524 V [Ie] 6 A Rated operational current [Ie]AC-15220 V 230 V 240 V [Ie] 6 A Rated operational current [Ie]AC-15380 V 400 V 415 V [Ie] 4 A Rated operational current [Ie]DC-1324 V [Ie] 3 A Rated operational current [Ie]DC-13110 V [Ie] 0.8 A Rated operational current [Ie]DC-13220 V [Ie] 0.3 A Supply....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSR-S02-1-I-CC/TKG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.