

INDUSTRIAL COMPONENT DATA

LSR-S11-1-I-CC/TKG 167678 EATON ELECTRIC

Hasp-operated safety switch (-40°C)

Brand: EATON - MOELLER | Manufacturer Part Number: LSR-S11-1-I-CC/TKG



Manufacturer	EATON - MOELLER
MPN / Reference	LSR-S11-1-I-CC/TKG
Catalog number	167678
Category	End switch
Minimum order	1 Pcs
Document ID	EO-39883B17C3
Generated	2026-08-05

Product Overview

Hasp-operated safety switch (-40°C)

Safety position switch Plastic 1 NO + 1 NC For lid Cold weather -40°C

Hasp-operated safety switch, LSR, Hasp-operated safety switch, Screw terminal, -40 - +70 °C

Hasp-operated safety switch, Basic function: Position switches, Safety position switches, Part group reference: LSR,

Product range: Hasp-operated safety switch, Degree of Protection: IP65, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series LSR Hasp-operated safety switch Catalog Number 167678 Model Code

LSR-S11-1-I-CC/TKG EAN 4015081642205 Product Length/Depth 160 mm Product Height 34 mm Product Width 30 mm

Product Weight 0.094 kg Certifications IEC/EN 60947 Features & Functions

Electric connection type Cable entry metrical Enclosure material Plastic Features Forced opening Switch function type

Slow-action switch General

Degree of protection IP65

NEMA 4X Operating frequency 1800 Operations/h Product category Hasp-operated safety switch Rated impulse withstand

voltage (Uimp) 6000 V AC Repetition accuracy 0.02 mm (Contacts/switching capacity) Suitable for Safety functions Type

Ambient conditions, mechanical

Mounting position As required Shock resistance 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms

Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (flexible with ferrule) 2 x (0.5 - 1.5) mm²

1 x (0.5 - 1.5) mm² Terminal capacity (solid) 1 x (0.75 - 2.5) mm²

2 x (0.75 - 1.5) mm² Electrical rating

Rated insulation voltage (Ui) 500 V Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 6 A Rated operational current (Ie) at AC-15, 24 V 6 A Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 4 A Rated operational current (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSR-S11-1-I-CC/TKG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.