

INDUSTRIAL COMPONENT DATA

LSR-S11-1-I-CC-TS 144119 EATON ELECTRIC Hinge-operated safety switch, 1N/O+1N/C, -40°C

Brand: EATON - MOELLER | Manufacturer Part Number: LSR-S11-1-I-CC-TS



Manufacturer	EATON - MOELLER
MPN / Reference	LSR-S11-1-I-CC-TS
Catalog number	144119
Category	Hinge switch
Minimum order	1 Pcs
Document ID	EO-EF9C4B1EA1
Generated	2026-08-05

Product Overview

Hinge-operated safety switch, 1N/O+1N/C, -40°C

Safety position switch Plastic 1 NO + 1 NC For hinge Cold weather -40°C

Hinge-operated safety switch, LSR, Safety hinge switch, Complete device, 1 N/O, 1 NC, Insulated material, Screwed terminal, -40 - +70 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Hinge-operated safety switch, LSR, Safety hinge switch, Complete device, 1 N/O, 1 NC, Insulated material, Screwed terminal, -40 - +70 °C Hinge-operated safety switch, Part group reference: LSR, Degree of Protection: IP65, Features: Complete device, Ambient temperature: -40 - +70 °C, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Contacts Notes = safety function, by positive opening to IEC/EN 60947-5-1, Housing: Insulated material, Connection type: Screwed terminal, Standards: IEC/EN 60947, Mounting position: As required Delivery program Basic function Position switches

Safety position switches Part group reference LSR Product range Safety hinge switch Degree of Protection IP65 Features Complete device Ambient temperature -40 - +70 °C Approval Contacts N/O = Normally open 1 N/O N/C = Normally closed 1 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Contact sequence Contact travel? = Contact closed? = Contact open Housing Insulated material Connection type Screwed terminal Technical data General Standards IEC/EN 60947 Climatic proofing Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30 Ambient temperature -40 - +70 °C Mounting position As required Degree of Protection IP65 Terminal

capacitiesSolid1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm²Terminal capacitiesFlexible with ferrule1 x (0.5 - 1.5)

2 x (0.5 - 1.5) mm²Repetition accuracy0.02 mmContacts/switching capacityRated impulse withstand voltage [Uimp]6000 V

ACRated insulation voltage [Ui]500 VRa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSR-S11-1-I-CC-TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.