

INDUSTRIAL COMPONENT DATA

LTS-100/C00/3-R 284690 EATON ELECTRIC NH fuse switch-disconnector, 125A, 500V, size 000, width 63 mm

Brand: EATON - MOELLER | Manufacturer Part Number: LTS-100/C00/3-R



Manufacturer	EATON - MOELLER
MPN / Reference	LTS-100/C00/3-R
Catalog number	284690
Category	Fuse switch disconnector
Minimum order	1 Pcs
Document ID	EO-BEFCB06477
Generated	2026-08-06

Product Overview

NH fuse switch-disconnector, 125A, 500V, size 000, width 63 mm

Base for fuses NH000

NH fuse switch-disconnector, 125 A, 500V, Size 000, width 63 mm, supplied without NH fuse-links, cable outlet at the bottom, ideal for use in service distribution boards conforming to EN 61439-2 due to space-saving width of only 63 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Industrial Fuse Bases
--------------	---

Additional Product Information

NH fuse switch-disconnector, 125A, 500V, size 000, width 63 mmNH fuse switch-disconnector, 125 A, 500V, Size 000, width 63 mm, supplied without NH fuse-links, cable outlet at the bottom, ideal for use in service distribution boards conforming to EN 61439-2 due to space-saving width of only 63 mm.Delivery program

Product range60 mm systemSubrangeNH fuse switch-disconnectorsDescriptionIncluding handguard at top and bottom Mounting without holesFunctionFor surface mounting on busbarsNumber of poles3 poleConnectionBox terminal 1.5...50 mm2

BottomInterval between busbar centres60 mmMax. fuse500 V125 AFrame sizeNH000For use with20 x 5/10 30 x 5/10For use withDouble T profileTechnical data

GeneralStandardsIEC/EN 60947-3Ambient temperature-25 - +55AltitudeMax. 2000 mInterval between busbar centres60 mmMounting positionVertical or horizontalOvervoltage category/pollution degreeIII/3Protection typeIP20 (Operating state) IP10 (Front cover open)Degree of protection, from the frontOperational stateIP20Degree of protection, from the frontFront cover openIP10Direction of incoming supplyas requiredLifespan, mechanical [Operations]1400Weight0.57

kgContactsRated operational voltage [Ue]500 V ACRated operational current [Ie]125 ARated frequency [f]40 - 60 HzRated conditional short-circuit current AC [Iq]50 kAeffUtilization category AC-22BRated making capacity300 AUtilization category AC-22BRated breaking capacity300 ALifespan, electrical [Operations]200Electrical? 200 OperationsLifespan, mechani...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LTS-100/C00/3-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.