

INDUSTRIAL COMPONENT DATA

M22-DDL-S-X226/X26 105227 Y7-105227 EATON ELECTRIC Pushbutton, double with led indicator Black (arrow) White..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DDL-S-X226/X26



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DDL-S-X226/X26
Catalog number	Y7-105227
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-97CDD9A2AC
Generated	2026-08-05

Product Overview

Pushbutton, double with led indicator; Black (arrow); White; Black (arrow); Highlighted

M22-DDL-S-X226/X26

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, black, black, inscribed, Bezel: titanium, arrow left/right

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Double actuator pushbutton Catalog Number 105227 Model Code

M22-DDL-S-X226/X26 EAN 4015081050253 Product Length/Depth 30 mm Product Height 55 mm Product Width 30 mm

Product Weight 0.015 kg Certifications UL Category Control No.: NKCR

CSA

UL

UL File No.: E29184

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

CSA File No.: 012528

CSA-C22.2 No. 14-05

CE

UL 508

IEC/EN 60947

VDE 0660

IEC/EN 60947-5

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Non-Flush

Classical Features Labelled Fitted with: Front ring Inscription Inscribed Lens color White General

Degree of protection NEMA 12

IP66

NEMA 3R

NEMA 13

NEMA 4X Degree of protection (front side) NEMA 4X

IP66 Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Product category RMQ-Titan Size Front

dimensions: 29,7 x 54,7 mm Suitable for Illumination Type Double actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuator color Black Actuator function Spring-return

Momentary Contacts

Force for positive....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DDL-S-X226/X26 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.