

INDUSTRIAL COMPONENT DATA

M22-DPL-W 173704 Y7-173704 EATON ELECTRIC Mushroom push-button 22 mm Return White Luminous Titanium Ring

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DPL-W



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DPL-W
Catalog number	Y7-173704
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-79F13F94EE
Generated	2026-08-06

Product Overview

Mushroom push-button; 22 mm; Return; White; Luminous; Titanium Ring

M22-DPL-W

Eaton Moeller® series M22 Mushroom actuator, RMQ-Titan, Mushroom, momentary, Mushroom black, White, Blank, Bezel: titanium

Mushroom actuator, Product range: RMQ-Titan, Single unit, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Mushroom actuator Catalog Number 173704 Model Code M22-DPL-W EAN 4015081701117 Product Length/Depth 37 mm Product Height 43 mm Product Width 37 mm Product Weight 0.016 kg

Certifications CSA Class No.: 3211-03

CSA file No. 012528

DNV

GL

IEC/EN 60947

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

LR

UL Category Control No.: NKCR

UL File No.: E29184

UL Listed

CSA certified

VDE 0660 Features & Functions

Bezel color Titanium Bezel material Plastic Design Classical

Mushroom-shaped Fitted with: Front ring Illumination Illuminated with LED element Inscription Blank Unlocking method

None General

Degree of protection IP67/IP69K

NEMA 4X, 13 Opening diameter 22.5 mm Operating frequency 3600 Operations/h Product category RMQ-Titan Suitable for Illumination Type Mushroom-headed pushbutton Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuating force 5 N Actuator color White Actuator function....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DPL-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.