

INDUSTRIAL COMPONENT DATA

M22-DRL-A 167431 Y7-167431 EATON ELECTRIC Illuminated pushbutton actuator, flush, amber, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DRL-A



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DRL-A
Catalog number	Y7-167431
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-7B665AA6D0
Generated	2026-08-02

Product Overview

Illuminated pushbutton actuator, flush, amber, maintained

M22-DRL-A

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Flush, maintained, orange, Blank, Bezel: titanium
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, maintained, button plate: orange,
Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with
SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function can be changed on device,
Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 167431 Model Code
M22-DRL-A EAN 4015081639311 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product
Weight 0.012 kg Certifications CSA-C22.2 No. 14-05

CSA File No.: 012528

CSA-C22.2 No. 94-91

UL File No.: E29184

UL

VDE 0660

CSA Class No.: 3211-03

IEC/EN 60947-5

UL 508

IEC/EN 60947

UL Category Control No.: NKCR

CE

CSA

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Flush

Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank

General

Degree of protection IP66

NEMA 4X

IP67

NEMA 13

NEMA 12

NEMA 3R

IP69K Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800

Operations/h Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Type Illuminated

pushbutton actuator Ambient conditions, mechanical

Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DRL-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.