

INDUSTRIAL COMPONENT DATA

M22-FI4 197234 Y7-197234 EATON ELECTRIC Surface mounting enclosure, flat, 4 mounting locations, M22

Brand: EATON - MOELLER | Manufacturer Part Number: M22-FI4



Manufacturer	EATON - MOELLER
MPN / Reference	M22-FI4
Catalog number	Y7-197234
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-FD03FC3A11
Generated	2026-08-05

Product Overview

Surface mounting enclosure, flat, 4 mounting locations, M22

M22-FI4

Eaton Moeller® series M22 Surface mounting enclosure, flat, 4 mounting locations, M22

Surface mounting enclosure, Housing: Insulated material, With high-grade steel screws, Number of locations: 4, Cable entry: rear: 1 x M20, lateral: 2 x M20 (1 x each side), Color RAL Value: RAL 7035, Color: Enclosure base anthracite, Connection to SmartWire-DT: no, For use with: 4 x 22.5, For use with: (Illuminated) pushbuttons, (Illuminated) selector switches, Key-operated pushbuttons, Indicator light, EMERGENCY-STOP/EMERGENCY OFF buttons with yellow label, Flat rear contact elements M22-FK..., Flat Rear LED elements M22-FLED-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Surface mounting enclosure Catalog Number 197234 Model Code M22-FI4 EAN 4015080893059 Product Length/Depth 279 mm Product Height 44 mm Product Width 43 mm Product Weight 0.201 kg Certifications CSA Class No.: 3211-03

CSA file No. 012528

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL File No.: E29184

UL Listed

CSA certified Features & Functions

Enclosure color Gray Enclosure material Plastic Fitted with: High-grade steel screws Knockouts 2 x M20 (cable entry knockout at the side, 1 x each side)

1 x M20 (cable entry knockouts at the rear) Number of locations 4 RAL-number 7035 General

Degree of protection NEMA 4X

IP67/IP69K Opening diameter 22.5 mm Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N

ETIM for 197234 Low-voltage industrial controls and switchgear (EC000200)

Feature Name

Feature Value

Number of command positions (EF001372)

4

Construction type housing (EF004008)

Surface mounting housing

Housing material (EF001596)

Plastic

Housing material quality (EF024143)

Other

Diameter openings (EF000243)

22.5 mm

Colour housing cover (EF001373)

Grey

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X

Width (EF000008)

43 mm

Height (EF000040)

44 mm

Depth (EF000049)

279 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-FI4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.