

INDUSTRIAL COMPONENT DATA

M22-FLED-G-HP 197143 Y7-197143 EATON ELECTRIC M22-FLED-G-HP

Brand: EATON - MOELLER | Manufacturer Part Number: M22-FLED-G-HP



Manufacturer	EATON - MOELLER
MPN / Reference	M22-FLED-G-HP
Catalog number	Y7-197143
Category	Lamp holder block for control circuit devices
Minimum order	1 Pcs
Document ID	EO-73F467189C
Generated	2026-08-06

Product Overview

M22-FLED-G-HP

Eaton Moeller® series M22 LED element, Flat Rear, green, front mounting, High Performance
LED element, Flat Rear, green, front mounting, High Performance

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory LED Catalog Number 197143 Model Code M22-FLED-G-HP EAN 4015080895244 Product Length/Depth 37.8 mm Product Height 14.4 mm Product Width 10 mm Product Weight 0.004 kg

Certifications CSA

UL

UL Category Control No.: NKCR

CSA Class No.: 3211-03

IEC/EN 60947-5

UL 508

CSA File No.: 012528

CSA-C22.2 No. 94-91

IEC 60947-5-1

CE

CSA-C22.2 No. 14-05

UL File No.: E29184 Features & Functions

Fitted with: Light source

Diode Light color Green General

Degree of protection IP20 Lifespan, electrical 100,000 h (at 25°C, according to EN60064) Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 4000 V AC Voltage type AC/DC Ambient conditions, mechanical Mounting position As required Shock resistance 50 g, Mechanical, according to IEC/EN 60068-2-27, Half-Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 85 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electro magnetic compatibility

Radiated RFI 10 V (IEC/EN 61131-2:2008, Level 3) Radio interference class Class A (EN 55011) Terminal capacities

Terminal capacity (flexible with ferrule) Use WAGO Variocrimp 4 crimping tool; please enquire for others

1 x (0.25 - 1) mm² Terminal capacity (solid) 1 x (0.75 - 1.5) mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-FLED-G-HP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.