

INDUSTRIAL COMPONENT DATA

M22-I1-* 197631 Y7-197631 EATON ELECTRIC M22-I1-*

Brand: EATON - MOELLER | Manufacturer Part Number: M22-I1-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22-I1-*
Catalog number	Y7-197631
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-3133640074
Generated	2026-08-03

Product Overview

M22-I1-*

Eaton Moeller® series M22 Surface mounting enclosure, 1 mounting location, M22

Housing: Insulated material, With high-grade steel screws, Individually markable with pushbutton configurator, Number of locations: 1, Cable entry: rear: 2 x M16, at top: 1 x M20, lateral: 2 x M20/M25 (1 x each side), Color RAL Value: RAL 7035, Color: Enclosure base anthracite, Connection to SmartWire-DT: no, For use with: 1 x 22.5, For use with: (Illuminated) pushbuttons, (Illuminated) selector switches, Key-operated pushbuttons, Indicator light, controlled stop/emergency-stop buttons with yellow label

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Surface mounting enclosure Catalog Number 197631 Model Code M22-I1-* Product Length/Depth 74 mm Product Height 72 mm Product Width 82 mm Product Weight 0.134 kg Compliances CE Catalog Notes Individually markable with pushbutton configurator Features & Functions Enclosure color Gray Enclosure material Plastic Fitted with: High-grade steel screws Knockouts 2 x M20/25 (cable entry knockout at the side, 1 x each side) 2 x M16 (cable entry knockouts at the rear) 1 x M20 (cable entry knockout at the top) Number of locations 1 RAL-number 7035 General Degree of protection NEMA 4X IP67/IP69K Opening diameter 22.5 mm Product category RMQ-Titan Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2

Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-I1-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.