

## INDUSTRIAL COMPONENT DATA

# M22-I2M/SS 118458 Y7-118458 EATON ELECTRIC Surface mounting enclosure, stainless steel, 2 mounting locations

Brand: EATON - MOELLER | Manufacturer Part Number: M22-I2M/SS



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | M22-I2M/SS                            |
| Catalog number  | Y7-118458                             |
| Category        | Enclosure for control circuit devices |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-9E0C32D18E                         |
| Generated       | 2026-08-05                            |

## Product Overview

Surface mounting enclosure, stainless steel, 2 mounting locations

M22-I2M/SS

Eaton Moeller® series M22 Surface mounting enclosure, stainless steel, 2 mounting locations

Surface mounting enclosure, Housing: Stainless steel, With high-grade steel screws, With mounting tabs on the sides, Number of locations: 2, Cable entry: -, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: no, For use with: 2 x 22.5, For use with: (Illuminated) pushbuttons, (Illuminated) selector switches, Key-operated pushbuttons, Indicator light, controlled stop/emergency-stop buttons with yellow label

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Surface mounting enclosure Catalog Number 118458 Model Code M22-I2M/SS EAN 4015081167258 Product Length/Depth 190 mm Product Height 84 mm Product Width 105 mm Product Weight 0.84 kg Compliances CE Features & Functions

Enclosure color Gray Enclosure material 316L stainless steel Fitted with: Mounting tabs on the sides

High-grade steel screws Number of locations 2 General

Degree of protection NEMA 4X

IP67/IP69K Opening diameter 22.5 mm Product category RMQ-Titan Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication  
Connection to SmartWire-DT No Contacts  
Force for positive opening - min 0 N Design verification  
Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2  
Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the  
the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the  
product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not  
apply, since the entire switchgear needs to be evaluated. 10....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-I2M/SS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.