

INDUSTRIAL COMPONENT DATA

M22-I4-* 197635 Y7-197635 EATON ELECTRIC M22-I4-*

Brand: EATON - MOELLER | Manufacturer Part Number: M22-I4-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22-I4-*
Catalog number	Y7-197635
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-CBFA20E9B1
Generated	2026-08-04

Product Overview

M22-I4-*

Eaton Moeller® series M22 Surface-mounting enclosure, RAL 7035, Individually markable with pushbutton configurator, Number of locations: 4, Cable entry: rear: 2 x M20, at top: 2 x M20, lateral: 2 x M20/M25 (1 x each side)
Housing: Insulated material, With high-grade steel screws, Individually markable with pushbutton configurator, Number of locations: 4, Cable entry: rear: 2 x M20, at top: 2 x M20, lateral: 2 x M20/M25 (1 x each side), Color RAL Value: RAL 7035, Color: Enclosure base anthracite, Connection to SmartWire-DT: no, For use with: 4 x 22.5, For use with: (Illuminated) pushbuttons, (Illuminated) selector switches, Key-operated pushbuttons, Indicator light, controlled stop/emergency-stop buttons with yellow label

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Surface mounting enclosure Catalog Number 197635 Model Code M22-I4-* Product Length/Depth 80 mm Product Height 56 mm Product Width 186 mm Product Weight 0.279 kg
Compliances CE Catalog Notes Individually markable with pushbutton configurator Features & Functions
Enclosure color Gray Enclosure material Plastic Fitted with: High-grade steel screws Knockouts 2 x M20 (cable entry knockouts at the rear)
2 x M20 (cable entry knockouts at the top)
2 x M20/25 (cable entry knockout at the side, 1 x each side) Number of locations 4 RAL-number 7035 General
Degree of protection NEMA 4X

IP67/IP69K Opening diameter 22.5 mm Product category RMQ-Titan Ambient conditions, mechanical
Mounting position As required Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication
Connection to SmartWire-DT No Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2
Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the
the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the
product standard's requirements. 10.2.4 Resistanc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-I4-* with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.