

INDUSTRIAL COMPONENT DATA

M22-L-W-GB5 186760 EATON ELECTRIC Indicator light, RMQ-Titan, Flush, white, inscribed, OFF

Brand: EATON - MOELLER | Manufacturer Part Number: M22-L-W-GB5



Manufacturer	EATON - MOELLER
MPN / Reference	M22-L-W-GB5
Catalog number	Y7-186760
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-127FCFF583
Generated	2026-08-04

Product Overview

Indicator light, RMQ-Titan, Flush, white, inscribed, OFF

Indicator light, Product range: RMQ-Titan, Single unit, Design: Flush, Color Lens: white, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Indicator light, RMQ-Titan, Flush, white, inscribed, OFFIndicator light, Product range: RMQ-Titan, Single unit, Design: Flush, Colour Lens: white, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Standards: IEC/EN 60947, VDE 0660Delivery program

Product rangeRMQ-TitanBasic functionIndicator lightsMounting hole diameter [?]22.5 mmSingle unit/Complete unitSingle unitDesignFlushColourLenswhiteLensButton plateinscribedDegree of ProtectionIP66, IP67, IP69Connection to SmartWire-DTyes

with SWD-RMQ connectionsTechnical data

GeneralStandardsIEC/EN 60947

VDE 0660Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP67, IP69Ambient temperatureOpen-25 - +70 °CMounting positionAs requiredMechanical shock resistance30

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 gTerminal capacitiesSolid0.5 - 1.5 mm²Terminal capacitiesStranded0.5 - 1.5 mm²shipping classificationDNV

GL

LRContactsRated impulse withstand voltage [Uimp]4000 V ACRated insulation voltage [Ui]250 VOvervoltage category/pollution degreeIII/3Design verification as per IEC/EN 61439

Technical data for design verificationOperating ambient temperature min.-25 °COperating ambient temperature max.+70 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-L-W-GB5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.