

INDUSTRIAL COMPONENT DATA

M22-LC-A 164376 Y7-164376 EATON ELECTRIC Indicator light, compact, flush, amber

Brand: EATON - MOELLER | Manufacturer Part Number: M22-LC-A



Manufacturer	EATON - MOELLER
MPN / Reference	M22-LC-A
Catalog number	Y7-164376
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-E180B7C84A
Generated	2026-08-03

Product Overview

Indicator light, compact, flush, amber

M22-LC-A

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Flush, without light elements, For filament bulbs, neon bulbs and LEDs up to 2.4 W, with BA 9s lamp socket, orange

Indicator light, compact, RMQ system, design: flush, lens amber, flush mounting plate, diameter 22.3mm, with lamp socket BA 9s max. 2.4W, degree of protection IP67, 69K

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Indicator light Catalog Number 164376 Model Code M22-LC-A EAN 4015081608829 Product Length/Depth 53 mm Product Height 30 mm Product Width 30 mm Product Weight 0.017 kg

Certifications IEC/EN 60947

CSA

CSA File No.: 012528

UL 508

UL File No.: E29184

CSA Class No.: 3211-03

UL

VDE 0660

UL Category Control No.: NKCR

CE

CSA-C22.2 No. 14-05

IEC/EN 60947-5 Catalog Notes Without light elements Features & Functions

Bezel color Chrome Bezel material Other Design Flush Fitted with: BA 9s lamp socket Lens color Orange General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front diameter: 29.7 mm Type Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity 0.5 - 1.5 mm², solid

0.5 - 1.5 mm², stranded Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design ver...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-LC-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.