

INDUSTRIAL COMPONENT DATA

M22-PV-ESS 178983 EATON ELECTRIC Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shap..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PV-ESS



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PV-ESS
Catalog number	Y7-178983
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-3D6B718B09
Generated	2026-08-05

Product Overview

Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Pull-to-release function, Red (RAL 3000), yellow

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Pull-to-release function, Red (RAL 3000), yellowEmergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Colour Mushroom head: Red, Colour Base: yellow, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 0660Delivery program Product rangeRMQ-TitanBasic functionControlled stop pushbuttons/emergency-stop buttonsMounting hole diameter [?]22.5

mmSingle unit/Complete unitSingle unitDesignMushroom-shapedDiameter [?]38
mmIlluminationNon-illuminatedPull-to-release functionDescriptionTamper-proof according to ISO 13850/EN
418ColourMushroom headRedBaseyellowRAL ValueRAL 3000Degree of ProtectionIP66, IP69Connection to
SmartWire-DTnoInstructionsMax. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11Technical data
GeneralStandardsIEC/EN 60947
VDE 0660Lifespan, mechanical [Operations]> 0.1 x 106Operating frequency [Operations/h]? 600Actuating force? 50
nClimatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP69Ambient temperatureOpen-25 - +70 °CMounting
positionAs requ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PV-ESS with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.