

INDUSTRIAL COMPONENT DATA

M22-PV30 197535 Y7-197535 EATON ELECTRIC Emergency Stop Mini Pushbutton D 30 mm Traction unlocking

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PV30



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PV30
Catalog number	Y7-197535
Category	Front element for mushroom push-button
Minimum order	5 Pcs
Document ID	EO-0F25528D2B
Generated	2026-08-05

Product Overview

Emergency Stop Mini Pushbutton; D=30 mm; Traction unlocking;
M22-PV30

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 30 mm, Non-illuminated, Pull-to-release function, Red, yellow

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 30 mm, Illumination: Non-illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP65, IP66, IP69, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: EN 50581:2012, EN 60947-5-1:2017, EN 60947-5-5:1997 + A1:2005 + A11:2013 + A2:2017, EN ISO 13850:2015, 2006/42/EC Machinery Directive

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 197535
Model Code M22-PV30 EAN 4015081942428 Product Length/Depth 30 mm Product Height 32 mm Product Width 30 mm
Product Weight 0.03 kg Certifications EN 50581

CE

EN ISO 13850

CSA

EAC

EN 60947-5-1

CCC

Machines 2006/42/EG

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking Features & Functions

Bezel color Other Base color Yellow Bezel material Other Design Mushroom-shaped

Classical Features Tamper-proof (according to ISO 13850, EN 418) Illumination Non-illuminated RAL-number 3000

Unlocking method Pull-release General

Degree of protection IP66

NEMA 4X Lifespan, mechanical 70,000 Operations Opening diameter 22.5 mm Operating frequency 600 Operations/h

Product category RMQ-Titan Size Front dimensions: 35 mm Suitable for Emergency stop Type Controlled stop

pushbutton/emergency-stop button Ambient conditions, mechanical

Mounting position As required Shock resistance 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT No Actuator

Actuating force 50 N Actuator color Red Actuator diameter 30 mm Actuator function Pull-to-release

Switching function latching Contacts

Force for positive....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PV30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.