

INDUSTRIAL COMPONENT DATA

M22-PVT30/FK02/FIY1 199353 EATON ELECTRIC Full Flat keypad Emergency stop button D 30 mm Interlocking by Giro..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVT30/FK02/FIY1



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVT30/FK02/FIY1
Catalog number	Y7-199353
Category	Control circuit devices combination in enclosure
Minimum order	1 Pcs
Document ID	EO-C36233741F
Generated	2026-08-05

Product Overview

Full Flat keypad; Emergency stop button; D=30 mm; Interlocking by Giro; 2 NC
Comp.dev.Emer.stop/em.swit.off but.encl.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Housing Catalog Number 199353 Model Code M22-PVT30/FK02/FIY1 EAN 4015081975990 Product Length/Depth 107 mm Product Height 76 mm Product Width 43 mm Product Weight 0.136 kg

Certifications CE

EAC

UL

CSA

CCC

CSA Class No.: 3211-03

CSA file No. 012528

DNV

GL

IEC/EN 60947

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

LR

UL Category Control No.: NKCR

UL File No.: E29184

UL Listed

CSA certified

VDE 0660 Features & Functions

Enclosure color Yellow Enclosure material Plastic General

Degree of protection IP Other

NEMA Other Opening diameter 22.5 mm Product category RMQ-Titan Suitable for Emergency stop Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Electrical rating

Rated control supply voltage (Us) at AC, 50 Hz - min 24 V Rated control supply voltage (Us) at AC, 50 Hz - max 230 V

Rated control supply voltage (Us) at AC, 60 Hz - min 24 V Rated control supply voltage (Us) at AC, 60 Hz - max 230 V

Rated control supply voltage (Us) at DC - min 24 V Rated control supply voltage (Us) at DC - max 220 V Communication

Connection to SmartWire-DT No Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 2 Number of contacts (normally open co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVT30/FK02/FIY1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.