

INDUSTRIAL COMPONENT DATA

M22-WJS4 178568 Y7-178568 EATON ELECTRIC Joystick 4 positions momentary metal shaft

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WJS4



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WJS4
Catalog number	Y7-178568
Category	Control switch, Joystick
Minimum order	1 Pcs
Document ID	EO-F89BF489EA
Generated	2026-08-04

Product Overview

Joystick; 4 positions; momentary; metal shaft

M22-WJS4

Eaton Moeller® series M22 Joystick, with one operating point per operating direction, with metal shaft, 4 positions, Bezel: titanium, momentary, in every position

Joystick, Product range: RMQ-Titan, Single unit, Description: with one operating point per operating direction, with metal shaft, 4 positions, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Function: momentary, in every position, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Joystick Catalog Number 178568 Model Code M22-WJS4 EAN 4015081738977

Product Length/Depth 100 mm Product Height 30 mm Product Width 30 mm Product Weight 0.028 kg Certifications CSA

File No.: 012528

UL 508

CSA Class No.: 3211-03

IEC/EN 60947

CSA-C22.2 No. 94-91

IEC/EN 60947-5

CE
CSA-C22.2 No. 14-13
UL
VDE 0660
CSA
UL File No.: E29184
UL Category Control No.: NKCR Features & Functions
Bezel color Titanium Bezel material Plastic Fitted with: Metal shaft
Filament bulb (24 V)
Retraction in 0-position
Front ring General
Degree of protection IP66
NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 2000
Operations/h Product Category RMQ-Titan Type Joystick Ambient conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Electrical rating
Rated operational current (Ie) at AC-21, 400 V, 415 V 0 A Communication
Connection to SmartWire-DT Yes
With SWD-RMQ connections Actuator
Actuating force 5 N Actuator function In every position
Momentary Number of actuation directions 4 Contacts
Force for positive opening - min 0 N
ETIM for 178568 Low-voltage....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WJS4 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.