

INDUSTRIAL COMPONENT DATA

M22-WRS3-RS 171153 Y7-171153 EATON ELECTRIC

Key-operated pushbutton (Ronis 455), 3 positions

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRS3-RS



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WRS3-RS
Catalog number	Y7-171153
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-426B1A61E7
Generated	2026-08-03

Product Overview

Key-operated pushbutton (Ronis 455), 3 positions

M22-WRS3-RS

Eaton Moeller® series M22 Key-operated actuator, maintained, 3 positions, Ronis 455, Key withdrawable: I, 0, II, Bezel: titanium

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Not suitable for master key systems, 3 positions, Lock mechanism: Ronis 455, I, II, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., with plunger bridge for the middle contact, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Key-operated actuator Catalog Number 171153 Model Code M22-WRS3-RS
EAN 4015081676439 Product Length/Depth 48 mm Product Height 59 mm Product Width 46 mm Product Weight 0.037 kg

Certifications CE

CSA

CSA Class No.: 3211-03

IEC/EN 60947-5

UL File No.: E29184

UL

UL Category Control No.: NKCR

CSA File No.: 012528

VDE 0660

CSA-C22.2 No. 14-05

IEC/EN 60947

UL 508

CSA-C22.2 No. 94-91

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Key operated

Classical Fitted with: Front ring

Plunger bridge for the middle contact Functions Stay-put/spring-return function, can be changed with coding parts

M22-XC-Y Key code Ronis 455 General

Accessories 2 keys included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side)

IP66 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 100 Operations/h

Operating torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Switching angle 60 ° Type Key-operated button Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRS3-RS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.