

INDUSTRIAL COMPONENT DATA

M22-WRS3-SA(*)-*A9 285539 Y7-285539 EATON ELECTRIC

Key-operated actuator, 3 positions, maintained, type acc..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRS3-SA(*)-*A9



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WRS3-SA(*)-*A9
Catalog number	Y7-285539
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-550E790611
Generated	2026-08-05

Product Overview

Key-operated actuator, 3 positions, maintained, type according to data

M22-WRS3-SA(*)-*A9

Key-operated actuator, RMQ-Titan, Key operated, maintained, Suitable for master key systems, 3 positions, Key withdrawable in position II, Bezel: titanium

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Suitable for master key systems, 3 positions, I, II, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, RMQ-Titan, Key operated, maintained, Suitable for master key systems, 3 positions, Key withdrawable in position II, Bezel: titaniumKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Suitable for master key systems, 3 positions, I, II, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66Delivery program

Product rangeRMQ-TitanBasic functionKey-operated buttonsSingle unit/Complete unitSingle unitDesignKey operatedmaintainedFunction: [= spring-return]60° ? 60°Suitable for master key systems3 positionsKey withdrawable in positionI0IIDegree of ProtectionIP66Front ringBezel: titaniumConnection to SmartWire-DTyes with SWD-RMQ connectionsFront dimensions29,7Information about equipment suppliedwith two keysTechnical data

General Standards IEC/EN 60947

VDE 0660 Lifespan, mechanical [Operations] > 0.1 x 10⁶ Operating frequency [Operations/h] ? 100 Ordering information for

users? 0.5 Nm Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66 Ambient temperature Open-25 - +70 °C Mounting position As
required Mechanical shock resistance 30

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 g shipping classification DNV

GL

LR Design verification as per IEC/EN 61439

Technical data for design verification Rated operational cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRS3-SA(*)-*-A9 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.