

**INDUSTRIAL COMPONENT DATA**

# M22-XAK40-GVP500 177703 Y7-177703 EATON ELECTRIC

## Controlled stop/Emergency switching off label, D 36mm, with..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XAK40-GVP500



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | M22-XAK40-GVP500               |
| Catalog number  | Y7-177703                      |
| Category        | Text plate for command devices |
| Minimum order   | 500 Pcs                        |
| Document ID     | EO-494403B2FF                  |
| Generated       | 2026-08-05                     |

### Product Overview

Controlled stop/Emergency switching off label, D = 36mm, with integrated yellow collar

M22-XAK40-GVP500

Eaton Moeller® series M22 Controlled stop/Emergency switching off label, D = 40mm, with integrated yellow collar

Emergency-Stop label, Product range: Accessories, Connection to SmartWire-DT: no

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

### Additional Product Information

**General specifications**

Product Name Eaton Moeller® series M22 Accessory Emergency-Stop label Catalog Number 177703 Model Code

M22-XAK40-GVP500 EAN 4015081722761 Product Length/Depth 36 mm Product Height 7 mm Product Width 36 mm

Product Weight 0.8 g Certifications UL/CSA certification not required Features & Functions

Color Yellow Inscription None Language Other RAL-number 1004 Shape Round General

Degree of protection IP69K

IP66

Depending on the used basic device

IP67 Product Category Accessories Size 40 x 40 mm Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole,

current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not apply, since the entire switchge...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XAK40-GVP500 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.