

INDUSTRIAL COMPONENT DATA

M22-XD-S-D3 218185 Y7-218185 EATON ELECTRIC

M22-XD-S-D3Q Button plate, flat black, UP

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XD-S-D3



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XD-S-D3
Catalog number	Y7-218185
Category	Legend plate for control circuit devices
Minimum order	10 Pcs
Document ID	EO-49A4933960
Generated	2026-08-03

Product Overview

M22-XD-S-D3Q Button plate, flat black, UP

M22-XD-S-D3

Button plate, flat black, UP

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Inscription: Auf, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Button plate, flat black, UPButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Inscription: Auf, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

General specificationsProduct nameEaton Moeller® series M22 Accessory Button platePart

no.M22-XD-S-D3EAN4015082181857Product Length/Depth24 millimetreProduct height3 millimetreProduct width24

millimetreProduct weight0.002 kilogramCertificationsUL/CSA certification not requiredProduct TradenameM22Product

TypeAccessoryProduct Sub TypeButton plateFeatures & FunctionsColorBlackDesignFlushInscriptionIndividual inscription possible: > 5 characters: letter height 3 mm

Individual inscription possible: <= 5 characters: letter height 5 mm

UpInscription typeTextLanguageGermanShapeRoundGeneral informationSuitable forPush buttonClimatic environmental

conditions Ambient operating temperature - min-25 °C Ambient operating temperature - max70 °C Communication Connection to SmartWire-DT No Design verification Equipment heat dissipation, current-dependent P_{vid0} W Heat dissipation capacity P_{diss0} W Heat dissipation per pole, current-dependent P_{vid0} W Rated operational current for specified heat dissipation (I_n)0 A Static heat dissipation, non-current-dependent P_{vs0} W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stabili...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XD-S-D3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.