

**INDUSTRIAL COMPONENT DATA**

# M22-XDH-B-D14 218234 M22-XDH-B-D14Q EATON ELECTRIC M22-XDH-B-D14Q Button plate, raised blue, RELEASE

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDH-B-D14



Entsperren

|                 |                                          |
|-----------------|------------------------------------------|
| Manufacturer    | EATON - MOELLER                          |
| MPN / Reference | M22-XDH-B-D14                            |
| Catalog number  | M22-XDH-B-D14Q                           |
| Category        | Legend plate for control circuit devices |
| Minimum order   | 1 Pcs                                    |
| Document ID     | EO-979F8C0BEE                            |
| Generated       | 2026-08-03                               |

## Product Overview

M22-XDH-B-D14Q Button plate, raised blue, RELEASE

Indicator plate. Salient. Blue. Registration: RELEASE

Button plate, raised blue, RELEASE

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Entsperren, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

## Additional Product Information

Button plate, raised blue, RELEASEButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Entsperren, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

Delivery program

Product rangeAccessoriesBasic function accessoriesButton plates for pushbutton actuatorsDescription? 5 characters: letter height 5 mm

&gt; 5 characters: letter height 3 mmDesignExtendedInscriptionEntsperrenSelection toTextFor use withM22(S)-D-X

M22(S)-DR-X

M22-DG-X

M30C-FD-X

M30C-FDR-XColour, symbolConnection to SmartWire-DTnoTechnical data  
GeneralAmbient temperatureOpen-25 - +70 °CDesign verification as per IEC/EN 61439  
Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+70 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verificat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDH-B-D14 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.