

INDUSTRIAL COMPONENT DATA

M22-XDH-S-D15 218235 M22-XDH-S-D15Q EATON ELECTRIC M22-XDH-S-D15Q Button plate, raised black, FORWARDS

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDH-S-D15



Vorwärts

Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDH-S-D15
Catalog number	M22-XDH-S-D15Q
Category	Legend plate for control circuit devices
Minimum order	1 Pcs
Document ID	EO-3909CA324A
Generated	2026-08-05

Product Overview

M22-XDH-S-D15Q Button plate, raised black, FORWARDS

Indicator plate. Salient. Black. Registration: FORWARDS

Button plate, raised black, FORWARDS

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Vorwärts, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Button plate, raised black, FORWARDSButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Vorwärts, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: noDelivery program

Product rangeAccessoriesBasic function accessoriesButton plates for pushbutton actuatorsDescription? 5 characters: letter height 5 mm

> 5 characters: letter height 3 mmDesignExtendedInscriptionVorwärtsSelection toTextFor use withM22(S)-D-X

M22(S)-DR-X

M22-DG-X

M30C-FD-X

M30C-FDR-XColour, symbolConnection to SmartWire-DTnoTechnical data
GeneralAmbient temperatureOpen-25 - +70 °CDesign verification as per IEC/EN 61439
Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+70 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verificatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDH-S-D15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.