

INDUSTRIAL COMPONENT DATA

M22-XDH-S-D18 218238 M22-XDH-S-D18Q EATON ELECTRIC M22-XDH-S-D18Q Button plate, raised black, DECREASE

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDH-S-D18



Senken

Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDH-S-D18
Catalog number	M22-XDH-S-D18Q
Category	Legend plate for control circuit devices
Minimum order	1 Pcs
Document ID	EO-372D4536A5
Generated	2026-07-29

Product Overview

M22-XDH-S-D18Q Button plate, raised black, DECREASE

Indicator plate. Salient. Black. Registration: DECREASE

Button plate, raised black, DECREASE

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Senken, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

Button plate, raised black, DECREASEButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Senken, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: noDelivery program

Product rangeAccessoriesBasic function accessoriesButton plates for pushbutton actuatorsDescription? 5 characters: letter height 5 mm

> 5 characters: letter height 3 mmDesignExtendedInscriptionSenkenSelection toTextFor use withM22(S)-D-X

M22(S)-DR-X

M22-DG-X

M30C-FD-X

M30C-FDR-XColour, symbolConnection to SmartWire-DTnoTechnical data
GeneralAmbient temperatureOpen-25 - +70 °CDesign verification as per IEC/EN 61439
Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+70 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDH-S-D18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.