

## INDUSTRIAL COMPONENT DATA

# M22-XDLH-R-X0 218161 Y7-218161 EATON ELECTRIC Lens, indicator Outgoing Red 0

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDLH-R-X0



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | M22-XDLH-R-X0                         |
| Catalog number  | Y7-218161                             |
| Category        | Hood/lens for circuit control devices |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-573FFED319                         |
| Generated       | 2026-08-04                            |

## Product Overview

Lens, indicator; Outgoing; Red; 0

M22-XDLH-R-X0

Eaton Moeller® series M22 Button lens, raised red

Button lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Name: STOP, Selection to: Symbol, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series M22 Accessory Button lens Catalog Number 218161 Model Code M22-XDLH-R-X0  
EAN 4015082181611 Product Length/Depth 24 mm Product Height 9 mm Product Width 24 mm Product Weight 0.002 kg

Certifications UL/CSA certification not required Features &amp; Functions

Design High Inscription Individual inscription possible: &lt;= 5 characters: letter height 5 mm

Individual inscription possible: &gt; 5 characters: letter height 3 mm Lens color Red Climatic environmental conditions

Ambient operating temperature - max 70 °C Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole,  
current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) 0 A 10.2.2 Corrosion resistance

Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product

standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated. 10.2.7 Inscriptions Meets the product standard's require...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDLH-R-X0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.