

## INDUSTRIAL COMPONENT DATA

# M22-XDLH-W-D17 218367 M22-XDLH-W-D17Q EATON ELECTRIC Button lens, raised white, raised

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDLH-W-D17



Heben

|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | M22-XDLH-W-D17                        |
| Catalog number  | M22-XDLH-W-D17Q                       |
| Category        | Hood/lens for circuit control devices |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-7D63E5A0C2                         |
| Generated       | 2026-08-05                            |

## Product Overview

Button lens, raised white, raised

Plate indicator transparent; Outgoing; White; Inscription: RAISED

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog pathEATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

Button lens, raised white, raisedButton lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Heben, Selection to: Text, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: noDelivery program

Product rangeAccessoriesBasic function accessoriesButton lensesDescription? 5 characters: letter height 5 mm  
> 5 characters: letter height 3 mmDesignExtendedInscriptionHebenSelection toTextFor use withM22(S)-DL-X  
M22(S)-DRL-X  
M22S-DGL-X  
M30C-FDL-X

M30C-FDRL-XColour, symbolConnection to SmartWire-DTnoTechnical data

GeneralAmbient temperatureOpen-25 - +70 °CDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating

ambient temperature max.+70 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDLH-W-D17 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.