

## INDUSTRIAL COMPONENT DATA

# M22-XDLH-W-D3 218360 Y7-218360 EATON ELECTRIC Button lens, raised white, AUF

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDLH-W-D3



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | M22-XDLH-W-D3                         |
| Catalog number  | Y7-218360                             |
| Category        | Hood/lens for circuit control devices |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-43635122E4                         |
| Generated       | 2026-08-05                            |

## Product Overview

Button lens, raised white, AUF

M22-XDLH-W-D3

Eaton Moeller® series M22 Button lens, raised white, AUF

Button lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Extended, Inscription: Auf, Selection to: Text, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Button lens Catalog Number 218360 Model Code M22-XDLH-W-D3  
EAN 4015082183608 Product Length/Depth 24 mm Product Height 9 mm Product Width 24 mm Product Weight 0.002 kg  
Certifications UL/CSA certification not required Features & Functions

Design Extended

High Features Labelled Inscription " AUF "

Individual inscription possible: <= 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm Inscription type Text Lens color White General

Product category Accessories Type Button lenses Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDLH-W-D3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.