

INDUSTRIAL COMPONENT DATA

M22-XDP-S-GB16 218292 Y7-218292 EATON ELECTRIC M22-XDP-S-GB16Q Button plate, mushroom black, REVERSE

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDP-S-GB16



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDP-S-GB16
Catalog number	Y7-218292
Category	Legend plate for control circuit devices
Minimum order	1 Pcs
Document ID	EO-16A83D415E
Generated	2026-08-06

Product Overview

M22-XDP-S-GB16Q Button plate, mushroom black, REVERSE

M22-XDP-S-GB16

Eaton Moeller® series M22 Button plate, mushroom black, REVERSE M22-XDP-S-GB16

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Inscription: REVERSE, Selection to: Text, For use with: M22(S)-D(R)P-..., Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Button plate Catalog Number 218292 Model Code M22-XDP-S-GB16

EAN 4015082182922 Product Length/Depth 24 mm Product Height 9 mm Product Width 24 mm Product Weight 0.002 kg

Certifications UL/CSA certification not required Features & Functions

Color Black Inscription Individual inscription possible: > 5 characters: letter height 3 mm

Individual inscription possible: <= 5 characters: letter height 5 mm

REVERSE Inscription type Text Language English Shape Round General

Product Category Accessories Suitable for Mushroom head push button Used with M22(S)-D(R)P-... Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDP-S-GB16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.