

INDUSTRIAL COMPONENT DATA

M22-XDP-S-GB18 218294 M22-XDP-S-GB18Q EATON ELECTRIC M22-XDP-S-GB18Q Button plate, mushroom black, LOWER

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDP-S-GB18



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDP-S-GB18
Catalog number	M22-XDP-S-GB18Q
Category	Legend plate for control circuit devices
Minimum order	1 Pcs
Document ID	EO-C363BD2806
Generated	2026-08-06

Product Overview

M22-XDP-S-GB18Q Button plate, mushroom black, LOWER

Indicator plate. Mushroom. Black. Registration: LOWER

Button plate, mushroom black, LOWER

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Inscription: LOWER, Selection to: Text, For use with: M22(S)-D(R)P-..., Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Button plate, mushroom black, LOWERButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Inscription: LOWER, Selection to: Text, For use with: M22(S)-D(R)P-..., Connection to SmartWire-DT: noDelivery program

Product rangeAccessoriesBasic function accessoriesButton plates for pushbutton actuatorsDescription? 5 characters: letter height 5 mm

> 5 characters: letter height 3 mmInscriptionLOWERSelection toTextFor use withM22(S)-D(R)P-...Colour, symbolConnection to SmartWire-DTnoTechnical data

GeneralAmbient temperatureOpen-25 - +70 °CDesign verification as per IEC/EN 61439

Technical data for design verification
Rated operational current for specified heat dissipation [In]0 A
Heat dissipation per pole, current-dependent [Pvid]0 W
Equipment heat dissipation, current-dependent [Pvid]0 W
Static heat dissipation, non-current-dependent [Pvs]0 W
Heat dissipation capacity [Pdiss]0 W
Operating ambient temperature min.-25 °C
Operating ambient temperature max.+70 °C
IEC/EN 61439 design verification
10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.
10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.
10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.
10.2 Strength of materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDP-S-GB18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.