

INDUSTRIAL COMPONENT DATA

M22S-PVL30 197541 Y7-197541 EATON ELECTRIC Emergency Stop Mini Pushbutton D 30 mm Luminous Unlocking by

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-PVL30



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-PVL30
Catalog number	Y7-197541
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-97C698E467
Generated	2026-08-06

Product Overview

Emergency Stop Mini Pushbutton; D=30 mm; Luminous; Unlocking by M22S-PVL30

HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, 30 mm, Illuminated with LED element, Pull-to-release function, Black, yellow, RAL 9005

HALT/STOP-Button, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 30 mm, Illumination: Illuminated with LED element, Pull-to-release function, Color Mushroom head: Black, Color Base: yellow, Color RAL Value: RAL 9005, RAL 9005, Degree of Protection: IP65, IP66, IP69, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 35, Instructions: Max. Configuration: 4 x M22-(C)K01, ...10 or 2 x M22-(C)K02, ...20, ...11 and 1 x M22-(F)LED..., When using M22-PVL... with 1 x M22-K01SMC10 (single channel), article M22-XSMC (order no.: 173030) is required. Order this item separately., Standards: EN 50581:2012 , EN 60947-5-1:2017, EN 60947-5-5:1997 + A1:2005 + A11:2013 + A2:2017, EN ISO 13850:2015, 2006/42/EC Machinery Directive

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 197541
Model Code M22S-PVL30 EAN 4015081942572 Product Length/Depth 30 mm Product Height 32 mm Product Width 30 mm Product Weight 0.03 kg Certifications EAC
CE

EN 60947-5-1

EN ISO 13850

CSA

EN 50581

CCC

Machines 2006/42/EG Features & Functions

Bezel color Other Base color Yellow Bezel material Other Color Black Design Mushroom-shaped

Classical Illumination Illuminated with LED element RAL-number 9005 Unlocking method Pull-release General

Degree of protection NEMA 4X

IP66 Lifespan, mechanical 70,000 Operations Opening diameter 22.5 mm Operating frequency 600 Operations/h Product

category RMQ-Titan Size Front dimensions: 35 mm Suitable for Illumination Type Ambient conditions, mechanical

Mounting position As required Shock resistance 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 50 N Actuator color Black Actuator diameter 30 mm Actuator function Pull-to-release

Switching function latching Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-PVL30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.