

INDUSTRIAL COMPONENT DATA

M22S-WRJS4 178567 Y7-178567 EATON ELECTRIC Joystick 4 positions stay-put metal shaft

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WRJS4



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WRJS4
Catalog number	Y7-178567
Category	Control switch, Joystick
Minimum order	1 Pcs
Document ID	EO-2F857D565A
Generated	2026-08-06

Product Overview

Joystick; 4 positions; stay-put; metal shaft

M22S-WRJS4

Eaton Moeller® series M22 Joystick, with one operating point per operating direction, with metal shaft, 4 positions, Bezel: black, maintained, in every position

Joystick, Product range: RMQ-Titan, Single unit, Description: with one operating point per operating direction, with metal shaft, 4 positions, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Function: maintained, in every position, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Joystick Catalog Number 178567 Model Code M22S-WRJS4 EAN

4015081738960 Product Length/Depth 95 mm Product Height 30 mm Product Width 30 mm Product Weight 0.028 kg

Certifications IEC/EN 60947

CSA-C22.2 No. 94-91

CSA File No.: 012528

UL Category Control No.: NKCR

CSA Class No.: 3211-03

UL

UL 508

CSA

UL File No.: E29184

CSA-C22.2 No. 14-13

VDE 0660

IEC/EN 60947-5

CE Features & Functions

Bezel color Black Bezel material Plastic Fitted with: Front ring

Filament bulb (24 V)

Metal shaft General

Degree of protection IP66

NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 2000

Operations/h Product Category RMQ-Titan Type Joystick Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated operational current (Ie) at AC-21, 400 V, 415 V 0 A Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuating force 5 N Actuator function Maintained

In every position Number of actuation directions 4 Contacts

Force for positive opening - min 0 N

ETIM for 178567 Low-voltage industrial controls and sw...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WRJS4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.