

INDUSTRIAL COMPONENT DATA

M30-FI4 197238 Y7-197238 EATON ELECTRIC Surface mounting enclosure, flat, 4 mounting locations, M30

Brand: EATON - MOELLER | Manufacturer Part Number: M30-FI4



Manufacturer	EATON - MOELLER
MPN / Reference	M30-FI4
Catalog number	Y7-197238
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-96D27DB2EA
Generated	2026-08-02

Product Overview

Surface mounting enclosure, flat, 4 mounting locations, M30

M30-FI4

Eaton Moeller® series M30 Surface mounting enclosure, Insulated material, With high-grade steel screws, Number of locations 4, 4 x 30.5

Surface mounting enclosure, Housing: Insulated material, With high-grade steel screws, Number of locations: 4, Cable entry: rear: 1 x M20, lateral: 2 x M20 (1 x each side), Color RAL Value: RAL 7035, Color: Enclosure base anthracite, Connection to SmartWire-DT: no, For use with: 4 x 30.5, For use with: (Illuminated) pushbuttons, (Illuminated) selector switches, Key-operated pushbuttons, Indicator light, EMERGENCY STOP/EMERGENCY OFF buttons with yellow set of adapter rings M22Y-R30, Flat rear contacts M22-FK..., Flat Rear LED elements M22-FLED-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Accessory Surface mounting enclosure Catalog Number 197238 Model Code M30-FI4 EAN 4015080893097 Product Length/Depth 279 mm Product Height 44 mm Product Width 43 mm Product Weight 0.201 kg Certifications CSA Class No.: 3211-03

CSA file No. 012528

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL File No.: E29184

UL Listed

CSA certified Features & Functions

Enclosure color Gray Enclosure material Plastic Fitted with: High-grade steel screws Knockouts 2 x M20 (cable entry knockout at the side, 1 x each side)

1 x M20 (cable entry knockouts at the rear) Number of locations 4 RAL-number 7035 General

Degree of protection NEMA 4X

IP67/IP69K Opening diameter 30 mm Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N

ETIM for 197238 Low-voltage industrial controls and switchgear (EC000200)

Feature Name

Feature Value

Number of command positions (EF001372)

4

Construction type housing (EF004008)

Surface mounting housing

Housing material (EF001596)

Plastic

Housing material quality (EF024143)

Other

Diameter openings (EF000243)

30 mm

Colour housing cover (EF001373)

Grey

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X

Width (EF000008)

43 mm

Height (EF000040)

44 mm

Depth (EF000049)

279 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30-FI4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.