

INDUSTRIAL COMPONENT DATA

M30C-FDL-A 182924 Y7-182924 EATON ELECTRIC Illuminated pushbutton actuators, Flat Front, flush, momentary, o..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FDL-A



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FDL-A
Catalog number	Y7-182924
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-2543484F48
Generated	2026-08-01

Product Overview

Illuminated pushbutton actuators, Flat Front, flush, momentary, orange, blank

M30C-FDL-A

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, Flat, momentary, orange, Blank, Metal bezel
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flat, momentary, button plate: orange,
Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with
SWD-RMQ connections, Front dimensions: Ø 36 mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 182924 Model Code
M30C-FDL-A EAN 4015081778515 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product
Weight 0.041 kg Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05 and 94-M91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Features & Functions

Bezel color Titanium Bezel material Metal Design Flat

Flat front Fitted with: Front ring Inscription Blank General

Degree of protection IP66

IP69K

IP67 Degree of protection (front side) IP67/IP69K

NEMA 4X, 13 Opening diameter 30.5 mm Product category RMQ-Titan Size Front dimensions: Ø 36 mm Suitable for Illumination Type Illuminated pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuator color Orange Actuator function Spring-return

Momentary Contacts

Force for positive opening - min 0 N

ETIM for 182924 Low-voltage industrial controls and s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FDL-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.