

INDUSTRIAL COMPONENT DATA

M30C-FDL-Y-X66 197204 EATON ELECTRIC Illuminated pushbutton actuator, Flat Front (drilling dimensions 30.5 m..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FDL-Y-X66



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FDL-Y-X66
Catalog number	Y7-197204
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-E8AD945F1C
Generated	2026-08-02

Product Overview

Illuminated pushbutton actuator, Flat Front (drilling dimensions 30.5 mm), Flush, momentary, yellow, inscribed, Metal bezel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Illuminated pushbutton actuator, Flat Front (drilling dimensions 30.5 mm), Flush, momentary, yellow, inscribed, Metal bezel
Delivery program

Product rangeFlat Front (drilling dimensions 30.5 mm)Basic functionIlluminated pushbutton actuatorsMounting hole diameter [?]30.5 mmSingle unit/Complete unitSingle unitDesignFlushmomentaryButton platebutton platyellowButton plateinscribedDegree of ProtectionIP66, IP67, IP69Front ringMetal bezelConnection to SmartWire-DTyes with SWD-RMQ connectionsTechnical data

GeneralStandardsIEC/EN 60947

VDE 0660Lifespan, mechanical [Operations]> 5 x 106Operating frequency [Operations/h]? 3600Actuating force? 5 nClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP67, IP69Ambient temperatureOpen-25 - +70 °CMounting positionAs requiredMechanical shock resistance15

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 gshipping classificationDNV

GLDesign verification as per IEC/EN 61439

Operating ambient temperature min.-25 °C Operating ambient temperature max.+70 °C Technical data ETIM 8.0
Low-voltage industrial components (EG000017) / Front element for push button (EC000221) Electric engineering,
automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for
push-button actuators () [AKF028014]) Colour button Yellow Number of command positions 1 Construction
type lens Round Hole diameter 30 mm Width opening 0 mm Height ope...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FDL-Y-X66 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.