

INDUSTRIAL COMPONENT DATA

M30C-FDRL-R-X0 182933 Y7-182933 EATON ELECTRIC

Illuminated pushbutton actuators, Flat Front, flush, maintain..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FDRL-R-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FDRL-R-X0
Catalog number	Y7-182933
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-EC5557E1F5
Generated	2026-08-02

Product Overview

Illuminated pushbutton actuators, Flat Front, flush, maintained, red, labeled

M30C-FDRL-R-X0

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, Flat, maintained, red, inscribed, Metal bezel
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flat, maintained, button plate: red, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 182933 Model Code M30C-FDRL-R-X0 EAN 4015081778607 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05 and 94-M91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified
ETIM for 182933 Low-voltage industrial controls and switchgear (EC000221)
Feature Name
Feature Value
Colour button (EF000190)
Red
Number of command positions (EF001372)
1
Construction type lens (EF006253)
Round
Hole diameter (EF000079)
30.5 mm
Width opening (EF004565)
0 mm
Height opening (EF004778)
0 mm
Type of button (EF001546)
Flat
Suitable for lighting (EF001142)
Yes
With protective cover (EF005500)
No
Labelled (EF001537)
Yes
Switching function latching (EF007447)
Yes
Spring-return (EF001407)
No
With front ring (EF006014)
Yes
Material front ring (EF005972)
Metal
Colour front ring (EF002429)
Chrome
Degree of protection (IP), front side (EF003118)
IP67/IP69K
Degree of protection (NEMA), front side (EF011961)
4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FDRL-R-X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.