

## INDUSTRIAL COMPONENT DATA

# M30C-FDRL-W-X0 182934 Y7-182934 EATON ELECTRIC

## Illuminated pushbutton actuators, Flat Front, flush, maintain..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FDRL-W-X0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | M30C-FDRL-W-X0                |
| Catalog number  | Y7-182934                     |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-B6C5A06861                 |
| Generated       | 2026-08-02                    |

### Product Overview

Illuminated pushbutton actuators, Flat Front, flush, maintained, white, labeled

M30C-FDRL-W-X0

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, Flat, maintained, White, inscribed 0, Metal bezel  
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flat, maintained, button plate: White,  
Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with  
SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function can be changed on  
device, Standards: IEC/EN 60947, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 182934 Model Code  
M30C-FDRL-W-X0 EAN 4015081778614 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm  
Product Weight 0.041 kg Certifications VDE 0660

IEC/EN 60947

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL  
IEC/EN 60947-5  
UL 508  
CSA-C22.2 No. 14-05 and 94-M91  
CE marking  
UL Category Control No.: NKCR  
UL Listed  
CSA certified  
ETIM for 182934 Low-voltage industrial controls and switchgear (EC000221)  
Feature Name  
Feature Value  
Colour button (EF000190)  
White  
Number of command positions (EF001372)  
1  
Construction type lens (EF006253)  
Round  
Hole diameter (EF000079)  
30.5 mm  
Width opening (EF004565)  
0 mm  
Height opening (EF004778)  
0 mm  
Type of button (EF001546)  
Flat  
Suitable for lighting (EF001142)  
Yes  
With protective cover (EF005500)  
No  
Labelled (EF001537)  
Yes  
Switching function latching (EF007447)  
Yes  
Spring-return (EF001407)  
No  
With front ring (EF006014)  
Yes  
Material front ring (EF005972)  
Metal  
Colour front ring (EF002429)  
Chrome  
Degree of protection (IP), front side (EF003118)  
IP67/IP69K  
Degree of protection (NEMA), front side (EF011961)  
4X, 13

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FDRL-W-X0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.