

INDUSTRIAL COMPONENT DATA

M30C-FL-A 183286 Y7-183286 EATON ELECTRIC Indicator light, Flat Front, flush, orange

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FL-A



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FL-A
Catalog number	Y7-183286
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-7AAD7002A1
Generated	2026-07-31

Product Overview

Indicator light, Flat Front, flush, orange

M30C-FL-A

Eaton Moeller® series M30 Indicator light, RMQ-Titan, Flat, orange, Metal bezel

Indicator light, Product range: RMQ-Titan, Single unit, Design: Flat, Color Lens: orange, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Indicator light Catalog Number 183286 Model Code M30C-FL-A EAN 4015081782277 Product Length/Depth 36 mm Product Height 32 mm Product Width 46 mm Product Weight 0.035 kg Certifications IEC/EN 60947

VDE 0660 Features & Functions

Bezel color Chrome Bezel material Metal Design Flat Fitted with: Front ring Lens color Orange General Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 30 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front dimensions: Ø 36 mm Type Indicator lights Ambient conditions, mechanical Mounting position As required Shock resistance Not planned Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity 0.5 - 1.5 mm², solid

0.5 - 1.5 mm², stranded Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Contacts

Force for positive opening - min 0 N

ETIM for 183286 Low-voltage industrial controls and switchgear (EC000223)

Feature Name

Feature Value

Suitable for number of built-in signal lights (EF006669)

1

Colour lens (EF000207)

Orange

Construction type lens (EF006253)

Round

Hole diameter (EF000079)

30 mm

Width opening (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FL-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.