

INDUSTRIAL COMPONENT DATA

M30C-FL-A-* 183292 Y7-183292 EATON ELECTRIC Indicator light, Flat Front, flush, orange, individual facility ..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FL-A-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FL-A-*
Catalog number	Y7-183292
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-D23E940B95
Generated	2026-08-04

Product Overview

Indicator light, Flat Front, flush, orange, individual facility for inscription

M30C-FL-A-*

Eaton Moeller® series M30 Indicator light, RMQ-Titan, Flat, orange, individual facility for inscription, Metal bezel
Indicator light, Product range: RMQ-Titan, Single unit, Design: Flat, Color Lens: orange, Button plate individual facility for inscription, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Indicator light Catalog Number 183292 Model Code M30C-FL-A-* Product Length/Depth 36 mm Product Height 32 mm Product Width 46 mm Product Weight 0.035 kg Certifications VDE 0660 IEC/EN 60947 Features & Functions

Bezel color Chrome Bezel material Metal Design Flat Fitted with: Front ring Inscription Individual inscription possible Lens color Orange General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 30 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front dimensions: Ø 36 mm Type Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance Not planned Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity 0.5 - 1.5 mm², solid

0.5 - 1.5 mm², stranded Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A 10.2.2 Corrosion re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FL-A-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.